



LINELL. CONVINCING ALL ALONG THE LINE.

- Flush-mounted linear inserts: inserts with opal cover, lens optic or wallwasher optic are flush with the track
- Opal optic for precise lines of light in the room
- With UGR 19, the lens optic meets the requirements for standard-compliant lighting in offices
- The wallwasher optic is ideal for displaying vertical objects
- Available in three lengths: 500 mm, 1,000 mm, 1,500 mm

www.trilux.com/linell



Detailed product information:
www.trilux.com/linell



LINELL

RAIL TRACK SYSTEM (STUCCHI)



Linell

Mounting type
Track

Functions
Accent lighting
General lighting

Light point height
up to 3.5 m

Beam characteristic
Lambertian
flood
very wide flood
wallwasher

Luminaire luminous flux
950 lm - 3,500 lm

Colour rendering index | Light colour
Ra > 80, Ra > 90
2,700 K
3,000 K
4,000 K

Service life
L80 = 50,000 h

Luminaire colour
black
white

Operating mode
switchable and DALI dimmable (ETDD)



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.