

LENTY.
PREMIUM CONCENTRATED ILLUMINATION.

- A versatile spotlight for retail, office and architecture with various beam characteristics
- Focused, glare-free light thanks to TRILUX ConVision® technology
- Three beam characteristics with luminous intensities from 1,000 lm to 2,000 lm
- Wide selection of light colours with a CRI > 90, ideal for a wide range of merchandise types
- Suitable for smart light management, either with control line or wireless
- The spotlight head swivels out to 50° and rotates through 355°

www.trilux.com/lenty-recessed

Detailed product information:
www.trilux.com/lenty-recessed

Lenty

Mounting type
Recessed

Functions
Accent lighting
General lighting

Light point height
2.8 - 4.5 m

Beam characteristic
spot
medium flood
flood

Luminaire luminous flux
1,000 lm - 2,000 lm

Colour rendering index | Light colour
Ra > 90
2,700 K
3,500 K
2,700 K - Brilliant Food (BF)
3,100 K - Brilliant Colour (BC)
3,200 K - Efficient White (EW)
4,000 K - Efficient Cool (EC)

Service life
L80 = 50,000 h

Luminaire colour
black
white

Operating mode
switchable and DALI dimmable (ETDD)
Bluetooth Low Energy (ETBLE)
switchable (ET)

Connectivity
Casambi capable

IP20



Also as a track spotlight

CONTACTS

TRILUX GmbH & Co. KG
Heidestrase · D-59759 Arnsberg
Postfach 19 60 · D-59753 Arnsberg
GERMANY
Tel. +49 2932 301-0
www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.
Şerifali Mah. Barbaros Cad. No 18
34775 Ümraniye Istanbul
TURKEY
Tel: +90 (216) 499 46 64
www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.