



4401. BRINGS METAL STRIP CEILINGS INTO THE FUTURE.

- Customised luminaire lengths, mounting concepts and lighting technologies specifically for metal strip ceilings make refurbishments simple and straightforward
- The 4401 G2 enables efficient 1:1 refurbishment of conventional luminaires in corridors, changing rooms, sanitary areas and canopied outdoor areas
- The 4401 G2 is particularly attractive economically due to its high efficiency, maintenance-friendly design and long service life

www.trilux.com/4401

Detailed product information:
www.trilux.com/4401













4401

RECESSED LUMINAIRES



4401

-  **Mounting type**
Recessed
-  **Mounting location**
Ceiling
-  **Beam characteristic**
wide
-  **Luminaire luminous flux**
1,000 - 4,000 lm
-  **Colour rendering index | Light colour**
Ra > 80
3,000 K
4,000 K
-  **Service life**
L80 = 60,000 h
-  **Luminaire colour**
white
-  **Operating mode**
switchable and DALI dimmable (ETDD)
switchable (ET)
-  **Additional equipment**
Single battery system, 3 hours
Switching relay for emergency power supply systems
-  **Accessories**
Removal tool
Fixing accessories
Spare parts
Replacement diffusers

   IP54

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.