



ONPLANA. RADIANCE TO GET EXCITED ABOUT.

- Wide range of variants each in three sizes and the option of ceiling, wall or pendant mounting
- The luminaire achieves an IP54 protection rating with use of a separate accessory
- The optical system with diffuser panel and microprismatics ensures uniform, glare-free light and maximum visual comfort

www.trilux.com/onplana

Detailed product information:
www.trilux.com/onplana



Onplana

- Mounting type**
Surface-mounted and suspended
- Mounting location**
Ceiling
Wall
- Design**
round
- Sizes**
234 mm, 316 mm, 445 mm
- Beam characteristic**
wide
- Luminaire luminous flux**
1,100 - 5,000 lm
- Colour rendering index | Light colour**
Ra > 80
3,000 K
4,000 K
Tunable White 2,700 K – 6,500 K
- Service life**
L85 = 50,000 h
L80 = 70,000 h
- Luminaire colour**
anthracite
white
- Operating mode**
switchable and DALI dimmable (ETDD)
switchable (ET)
- Connectivity**
Casambi capable (on request)
- Additional equipment**
Single battery system, 3 hours
- Accessories**
Sealings
Wire suspensions and mains cables

IP40

ONPLANA

DOWNLIGHTS



Simply attractive – the flexible adaptation artists



IP54 for ceiling mounting

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.