



SO-TUBE G3. INDUSTRIAL STYLE MEETS NEW WORK.

- The robust charm of the design blends ideally into industrial-style office environments
- Modern LED technology with linear lighting design and a round light emission surface, also with UGR 19
- Diverse mounting types provide creative options for design

www.trilux.com/sotube-led

Detailed product information:
www.trilux.com/sotube-led



SO-TUBE G3
SURFACE-MOUNTED LUMINAIRES



So-Tube G3

- Mounting type**
Surface-mounted
- Mounting location**
Wall
Ceiling
- Beam characteristic**
Lambertian
- Luminaire luminous flux**
7,800 lm
- Colour rendering index | Light colour**
Ra > 80
3,000 K
4,000 K
Tunable White 2,700 K- 6,500 K
- Service life**
L80 = 50,000 h
- Luminaire colour**
black
- Operating mode**
switchable and DALI dimmable (ETDD)
- Connectivity**
LiveLink capable
LiveLink WiFi-capable
- Additional equipment**
UGR 19 variants with glass optic available in all lengths
- Accessories**
Connection cables
Ceiling roses
Ceiling roses with LiveLink ceiling roses with LiveLink WiFi connection cables

IP20



Round light emission surface



Also available as suspended luminaire

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.