



LUNEXO H. SMARTER LIGHT FOR INCREASED COMFORT.

- Outstanding quality of light thanks to uniform light emission surface with all-round light edge
- Rooms are bathed in soft light and visually upgraded
- Perfectly controllable lighting design, ranging from fully automatic with daylight and presence detection and Smart Device connection to manual operation
- The light colour and light intensity as well as the direct and indirect light component can be separately controlled for individual well-being

www.trilux.com/lunexo

Detailed product information:
www.trilux.com/lunexo



LUNEXO H

SUSPENDED LUMINAIRES



Lunexo H

- Mounting type**
Suspended
- Mounting location**
Ceiling
- Size**
linear
- Beam characteristic**
wide
direct-indirect
- Luminaire luminous flux**
6,500 - 8,800 lm
- Colour rendering index | Light colour**
Ra > 80
3,000 K
4,000 K
Tunable White 2,700 K - 6,500 K
- Service life**
L80 = 70,000 h
- Luminaire colour**
silver-grey
white
- Operating mode**
switchable and DALI dimmable (ETDD)
- Connectivity**
LiveLink integrated
Casambi capable
- Additional equipment**
LiveLink sensor IR Micro for daylight-dependent control and presence detection
- Accessories**
Ceiling roses
Ceiling roses with LiveLink



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.