



ACQUEX. THE STRONG EX SOLUTION FOR A SAFE START.

- Acquex is a robust entry-level solution for ATEX zones 2/22
- Ex-certified components, Ex standard-compliant mounting and the technical concept of the luminaire guarantee protection for industrial ATEX zones
- Can be optionally mounted as a wall or ceiling luminaire and features simple and safe installation (Ex cable gland)
- High impact resistance (IK10), up to 8,000 lm, versions available with DALI and emergency light battery
- Long life cycles of up to 100,000 hours and therefore maximum savings in terms of maintenance costs

www.trilux.com/atex

Detailed product information:
www.trilux.com/atex



ACQUEX

LUMINAIRES WITH HIGHER PROTECTION RATING



Acquex

ATEX designation
Gas: II 3G Ex ec IIC T6 Gc
Dust: II 3D Ex tc IIIC T85°C Dc

Mounting type
Surface-mounted

Mounting location
Ceiling
Wall
Outdoor ceiling

Beam characteristic
Lambertian

Luminaire luminous flux
2,000 - 8,000 lm

Colour rendering index | Light colour
Ra > 80
3,000 K
4,000 K

Service life
L80 = 70,000 h

Luminaire colour
signal yellow

Operating mode
switchable and DALI dimmable (ETDD)
switchable (ET)

Additional equipment
Single battery system, 3 hours

Accessories
Steel strip suspensions

CE IP66



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.