



DUROXO G2. GAS-RESISTANT SOLUTION FOR SPECIAL AREAS.

- Gas-resistant lighting solution for use in gaseous or solvent-containing atmospheres as caused by sulphur fumes or ammonia fumes
- Ideal for e.g. tyre warehouses, non-canopied outdoor areas and special industrial areas
- Extremely long service life of 100,000 h (L80 at tq 35°C)
- Robust PMMA housing, protection rating IP69K, extremely high impact resistance

www.trilux.com/duroxo-led

Detailed product information:
www.trilux.com/duroxo-led



DUROXO G2

LUMINAIRES WITH HIGHER PROTECTION RATING



Duroxo G2

Mounting type
Surface-mounted
Suspended

Mounting location
Wall
Ceiling
Outdoor wall, canopied
Outdoor ceiling
Outdoor, not canopied

Beam characteristic
wide

Luminaire luminous flux
6,700 lm

Colour rendering index | Light colour
Ra > 80
4,000 K

Operating mode
switchable and DALI dimmable (ETDD)
switchable (ET)

Accessories
Fixing accessories



Completely gas-tight lighting solution

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.