



FIDESCA-SD. PREMIUM QUALITY FOR CLEANROOMS.

- Ideally suited for use in critical production and laboratory environments, cleanroom suitability certified by TÜV Süd
- With laminated safety glass covers and IP65 protection on the room side, luminaires meet all requirements for safe work surroundings
- Easy-to-clean luminaire
- Sustainable lighting concept enables retroactive replacement of the light engine

www.trilux.com/fidescasd



Detailed product information:
www.trilux.com/fidescasd



Fidesca SD G4

- Mounting type**
Surface-mounted
Recessed
- Mounting location**
System ceiling with exposed grids
System ceiling with concealed grids
Ceiling
- Design**
square
linear
- Beam characteristic**
wide
lambertian
narrow
- Luminaire luminous flux**
5,500 - 20,000 lm
- Colour rendering index | Light colour**
Ra > 90
4,000 K
6,500 K
Tunable White 2,700 K - 6,500 K
- Service life**
L80 (tq 40 °C) = 100,000 h
- Luminaire colour**
white
- Operating mode**
switchable and DALI dimmable (ETDD)
- Connectivity**
LiveLink integrated
LiveLink WiFi
- Accessories**
Recessing frame
Mounting accessories
Diffuser removal tool

IP65 (on room side)

FIDESCA-SD

LUMINAIRES WITH HIGHER PROTECTION RATING



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.