8841 LS. AN ELEGANT LIGHT COLUMN FOR PRESTIGIOUS TASKS.

- On the slender light column, the transitions between supporting column and luminaire head are hardly visible
- Thanks to innovative MLT IQ technology, the light effects can be individually adapted to on-site needs via the light distribution properties
- The light column is optionally available with a height of 2.60 m or 3.60 m
- The 8841 LS is part of an overall product range also containing bollards and wall solutions
- A version with continuous underground support provides additional protection from vandalism

www.trilux.com/8841LS

Detailed product information:
www.trilux.com/8841LS

8841 LS

Mounting type
Outdoor free-standing mounting

Mounting location
Outdoor ground

Beam characteristic
asymmetric wide
rotationally symmetric wide

Luminaire luminous flux
1,000 - 3,500 lm

Colour rendering index | Light colour
Ra > 70
3,000 K
4,000 K

Service life
L80 = 80,000 h

Luminaire colour
anthracite

Operating mode
switchable (ET)

Accessories
Shieldings
Underground supports

CE UKCA IP65

Complete range, also available as bollard luminaires

CONTACTS

TRILUX GmbH & Co. KG
Heidestrase · D-59759 Arnsberg
Postfach 19 60 · D-59753 Arnsberg
GERMANY
Tel. +49 2932 301-0
www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.
Şerifali Mah. Barbaros Cad. No 18
34775 Ümraniye Istanbul
TURKEY
Tel: +90 (216) 499 46 64
www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.