

LUTERA. THE COMPLETE RANGE FOR PERFECT PRESENTATIONS.

- A flexible family of ground-recessed luminaires with three sizes, various luminous flux packages and various beam characteristics
- Simple mounting thanks to low recess depth
- Intelligent sealing concept for long-term fault-free operation
- Ideal for the attractive, individual presentation of outdoor areas around buildings such as facades, objects and surfaces

www.trilux.com/lutera

Detailed product information:
www.trilux.com/lutera



LUTERA

GROUND-RECESSED LUMINAIRES



Lutera

Mounting type
Outdoor ground-recessed

Mounting location
Outdoor ground

Beam characteristic
rotationally symmetric wide
rotationally symmetric narrow
rotationally symmetric medium wide
asymmetric

Luminaire luminous flux
120 - 2,900 lm

Colour rendering index | Light colour
Ra > 80
3,000 K
4,000 K
amber
blue
green
red

Service life
L80 = 50,000 h

Luminaire colour
black

Operating mode
switchable and DALI dimmable
forward phase control (ETD)
switchable (ET)

Accessories
Cover glasses
Cover plates
Ground mounting enclosure
Sealings
Filters
Connections

CE IP68

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.