

## SKEO R. A LIGHT COMPONENT FOR STRIKING BUILDING AND PATH LIGHTING.

- Wide design scope meeting the most diverse lighting requirements thanks to various lumen packages
- Numerous distribution characteristics, two different sizes and single or double light emission
- Purist design blends into the surroundings
- High-quality die-cast aluminium housing makes the luminaire resistant against environmental and weather factors

[www.trilux.com/skeor](http://www.trilux.com/skeor)

Detailed product information:  
[www.trilux.com/skeor](http://www.trilux.com/skeor)



SKEO R

WALL AND CEILING LUMINAIRES



Frosted or transparent glass



Variety of distribution characteristics

### Skeo R

**Mounting type**  
Surface-mounted

**Mounting location**  
Outdoor wall  
Outdoor ceiling

**Beam characteristic**  
asymmetric wide  
symmetric narrow

**Luminaire luminous flux**  
600 - 4,000 lm

**Colour rendering index | Light colour**  
Ra > 70  
3,000 K

**Service life**  
L80 = 50,000 h

**Luminaire colour**  
anthracite

**Operating mode**  
switchable (ET)

CE UK IP65

# CONTACTS

## **TRILUX GmbH & Co. KG**

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

[www.trilux.com/en](http://www.trilux.com/en)

## **SiSEL Mühendislik Elektronik San. ve Tic. A.ş.**

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

[www.endalight.com](http://www.endalight.com)

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.