



RAIL. INVISIBLE CONNECTION. VISIBLE IMPACT.

- Rail bundles flexible power supply and control lines for luminaires in a slender aluminium profile
- The profile contains 6 conductors for 3 separately switched luminaire groups and DALI control lines for light management
- Rail features a high-quality fine surface structure
- Available for surface-mounting, recessing or flush mounting and as a suspended version (optionally also with indirect component)

www.trilux.com/rail

Detailed product information:
www.trilux.com/rail



RAIL TRACK SYSTEM (STUCCHI)

RAIL TRACK SYSTEM (STUCCHI)



Rail

- 🔧 Mounting type**
Surface-mounted
Recessed
Flush-mounted
Suspended

- ↔ Length**
Surface-mounted | Recessed |
Flush-mounted
1,000 mm
2,000 mm
3,000 mm
4,000 mm
Suspended
1,405 mm
1,500 mm with feeder
2,810 mm
2,905 mm with feeder

- 👤 Mounting location**
Ceiling

- 🎨 Track colour**
white
black
further colours on request

- 🔌 Operating mode**
switchable and DALI dimmable (ETDD)

- ⊕ Accessories**
Covers
Fixing accessories
Blanking covers
Ceiling roses
Sealings
Feed-in accessories
End caps
Couplings
Mounting accessories
Pendant suspensions
Wire suspensions
Track connector
Sealing caps



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.