



BELVISO C. THE STANDARD FOR EFFICIENCY AND ECONOMY.

- With exclusive light frame (C2 versions)
- Completely uniform illumination creates a feel-good atmosphere at workstations via shadow-free light
- Coloured light guides enable individual light atmospheres and an emotional upgrading of the lighting design

www.trilux.com/belviso-c1
www.trilux.com/belviso-c2

Detailed product information:
www.trilux.com/belviso-c1
www.trilux.com/belviso-c2



Belviso C

- Mounting type**
Recessed
Semi-recessed
- Mounting location**
System ceiling with exposed grids
System ceiling with concealed grids (M84)
Ceiling
- Design**
square
linear
- Beam characteristic**
wide
- Luminaire luminous flux**
3,900 - 4,050 lm
- Colour rendering index | Light colour**
Ra > 80
3,000 K
4,000 K
Tunable White 3,000 K - 6,500 K
Further light colours on request
- Service life**
L80 = 70,000 h
- Luminaire colour**
white
- Operating mode**
switchable and DALI dimmable (ETDD)
switchable (ET)
- Additional equipment**
with coloured light frame
- Accessories**
Fixing accessories



Also available as surface-mounted version, see page 146.

BELVISO C

RECESSED LUMINAIRES



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.