



VALINEO. THE BASIC SOLUTION FOR PLANAR LIGHT IN PROJECT BUSINESS.











- An attractive basic solution for sophisticated project business
- An investment that pays: energy efficiency of 180 lm/W and a 70,000 hour service life ensure low operating costs in the long run
- High quality of materials and workmanship
- An ideal refurbishment solution thanks to simple mounting and Plug & Play installation
- Planning flexibility thanks to Multilumen technology

www.trilux.com/valineo

Detailed product information:
www.trilux.com/valineo



Valineo G4

-  **Mounting type**
Recessed
-  **Mounting location**
System ceiling with exposed grids
Ceiling
-  **Design**
square
-  **Beam characteristic**
wide
-  **Luminaire luminous flux**
3,800 - 5,000 lm
-  **Colour rendering index | Light colour**
Ra > 80
3,000 K
4,000 K
Tunable White 2,700 K – 6,000 K
-  **Service life**
L80 = 70,000 h
-  **Luminaire colour**
white
-  **Operating mode**
switchable and DALI dimmable (ETDD)
switchable (ET)
-  **Accessories**
Surface-mounting frame
Mounting accessories

      IP20

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.