



## LENTY. THE UNIVERSAL LENS SPOTLIGHTS.

- A versatile spotlight for retail, office and architecture with various sizes and beam angles
- Focused, glare-free light thanks to TRILUX ConVision® technology
- Three sizes with luminous intensities from 500 lm to 4,000 lm
- Wide selection of light colours, also with a CRI > 90, ideal for a wide range of merchandise types
- Easy and precise alignment, and even suspended tracks stay in balance thanks to the balanced centre of gravity
- The Track Driver largely disappears and the Invisible Driver completely disappears into the track profile

[www.trilux.com/lenty-rail](http://www.trilux.com/lenty-rail)  
[www.trilux.com/lenty-mini-rail](http://www.trilux.com/lenty-mini-rail)

Detailed product information:  
[www.trilux.com/lenty-rail](http://www.trilux.com/lenty-rail)  
[www.trilux.com/lenty-mini-rail](http://www.trilux.com/lenty-mini-rail)



### Lenty Mini Lenty Track

**Mounting type**  
Track

**Functions**  
Accent lighting  
General lighting

**Light point height**  
2.8 - 4.5 m

**Beam characteristic**  
spot  
medium flood  
flood

**Luminaire luminous flux**  
500 lm - 1,000 lm (Lenty Mini)  
1,000 lm - 2,000 lm (Lenty Track)

**Colour rendering index | Light colour**  
Ra > 80  
2,700 K  
3,000 K  
3,500 K  
4,000 K  
Ra > 90  
2,700 K - Brilliant Food (BF)  
3,100 K - Brilliant Colour (BC)  
3,200 K - Efficient White (EW)  
4,000 K - Efficient Cool (EC)

**Service life**  
L80 = 50,000 h

**Luminaire colour**  
black with black limiter  
black with white limiter  
white with black limiter  
white with white limiter

**Operating mode**  
switchable and DALI dimmable (ETDD)  
Bluetooth Low Energy (ETBLE)  
switchable (ET)

**Connectivity**  
Casambi capable

IP20

LENTY

RAIL TRACK SYSTEM (STUCCHI)



# CONTACTS

## **TRILUX GmbH & Co. KG**

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

[www.trilux.com/en](http://www.trilux.com/en)

## **SiSEL Mühendislik Elektronik San. ve Tic. A.ş.**

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

[www.endalight.com](http://www.endalight.com)

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.