



## MONDIA G3. FUNCTIONALITY IN A TIMELESS DESIGN.

- Rapid installation, low maintenance and energy efficiency
- Low investment costs with quick payback
- Flexible uses as ceiling or wall luminaire, in three diameters and three luminous flux packages – switchable and dimmable
- Equally ideal for office, education, health and care applications

[www.trilux.com/mondia](http://www.trilux.com/mondia)

Detailed product information:  
[www.trilux.com/mondia](http://www.trilux.com/mondia)



MONDIA G3

WALL AND CEILING LUMINAIRES



### Mondia G3

- Mounting type**  
Surface-mounted
- Mounting location**  
Ceiling  
Wall
- Beam characteristic**  
Lambertian
- Luminaire luminous flux**  
1,300 - 3,200 lm
- Colour rendering index | Light colour**  
Ra > 80  
3,000 K  
4,000 K
- Service life**  
L80 = 50,000 h
- Luminaire colour**  
White
- Operating mode**  
Switchable and DALI dimmable (ETDD)  
Switchable (ET)
- Additional equipment**  
Motion sensor  
Single battery system, 3 hours
- Accessories**  
Decorative attachments

CE UK IP40

# CONTACTS

## **TRILUX GmbH & Co. KG**

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

[www.trilux.com/en](http://www.trilux.com/en)

## **SiSEL Mühendislik Elektronik San. ve Tic. A.ş.**

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

[www.endalight.com](http://www.endalight.com)

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.