



DEVEO FIT. A ROBUST WEATHER-PROOF ENTRY-LEVEL LED LUMINAIRE.

- Ideal for quick installation, with easy replacement of many conventional weather-proof luminaires thanks to maximum flexibility when attaching the fixing clips
- Intuitive quick connection system for maximum time savings during installation
- Basic solution with low investment and operating costs
- Gas-resistant solutions for more demanding applications available in the portfolio
- PMMA versions enable use in aggressive environments with gases and vapours, and ensure robustness when treated with cleaning agents

www.trilux.com/deveo

Detailed product information:
www.trilux.com/deveo



DEVEO FIT

LUMINAIRES WITH HIGHER PROTECTION RATING



Deveo Fit

Mounting type
Suspended
Surface-mounted

Mounting location
Ceiling
Wall
Outdoor wall, canopied
Outdoor ceiling
Outdoor, not canopied (IP69K)

Beam characteristic
Lambertian

Luminaire luminous flux
2,100 - 6,000 lm

Colour rendering index | Light colour
Ra > 80
4,000 K

Service life
L80 = 50,000 h

Luminaire colour
light grey

Operating mode
switchable and DALI dimmable (ETDD)
switchable (ET)

Additional equipment
Through-wiring
IP69K

Accessories
Mounting accessories

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.