



## MIRONA FIT R. HIGH-BAY IN ROUND PERFECTION.

- Direction-independent with a minimalist design, and ideally suited for various applications
- Especially reliable under challenging conditions in the industrial sector due to high protection rating and temperature resistance
- Outstanding light: with its high efficiency (up to 187 lm/W) and long service life (70,000 h at tq 50°C), Mirona Fit R guarantees continuously low operating costs

[www.trilux.com/mirona-fit-led](http://www.trilux.com/mirona-fit-led)

Detailed product information:  
[www.trilux.com/mirona-fit-led](http://www.trilux.com/mirona-fit-led)



MIRONA FIT R

HIGH-BAY LUMINAIRES



### Mirona Fit R

- Mounting type**  
Surface-mounted  
Suspended
- Mounting location**  
Wall  
Ceiling
- Beam characteristic**  
wide  
narrow
- Luminaire luminous flux**  
15,000 - 35,000 lm
- Colour rendering index | Light colour**  
Ra > 80  
4,000 K  
6,500 K
- Service life**  
L80 (tq 50 °C) = 70,000 h
- Luminaire colour**  
white
- Operating mode**  
switchable and DALI dimmable (ETDD)  
switchable (ET)
- Connectivity**  
Monitoring ready  
Smart lighting ready
- Accessories**  
Fixing hardware  
Fixing bracket  
Chains  
Reflectors



# CONTACTS

## **TRILUX GmbH & Co. KG**

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

[www.trilux.com/en](http://www.trilux.com/en)

## **SiSEL Mühendislik Elektronik San. ve Tic. A.ş.**

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

[www.endalight.com](http://www.endalight.com)

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.