

8841. POWERFUL WITH STYLE AND SMART FUNCTIONS.

- Thanks to its classic design, 8841 blends harmoniously into the building environment and sets visual accents
- The multi-lens technology (MLT[®]) guarantees standard-compliant illumination even at wide light point spacing of up to 14 metres
- Smart additional functions in the supporting column
- With versions with 180° shading, the proportion of light emitted to the rear is 0 %

www.trilux.com/8841

Detailed product information:
www.trilux.com/8841



8841

BOLLARD LUMINAIRES



8841

- Mounting type**
Outdoor free-standing mounting
- Mounting location**
Outdoor ground
- Beam characteristic**
asymmetric wide
rotationally symmetric wide
- Luminaire luminous flux**
700 - 850 lm
- Colour rendering index | Light colour**
Ra > 70
3,000 K
4,000 K
- Service life**
L80 = 100,000 h
- Luminaire colour**
anthracite
- Operating mode**
switchable and DALI dimmable (ETDD)
- Additional equipment**
PIR sensors
- Accessories**
Underground supports
Underground support with continuous supporting column
Supporting column with socket
Supporting column with sensor

CE UK IP65

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.