

## ALTIGO WD. LIGHT LINE FOR ILLUMINATING PATHS AND FACADES.

- Diverse uses thanks to various lengths, selectable optics and several mounting options
- Slender, flat design for installation in difficult-to-access locations with low mounting space
- Robust and durable due to selected materials and high-quality workmanship

[www.trilux.com/altigog2](http://www.trilux.com/altigog2)

Detailed product information:  
[www.trilux.com/altigog2](http://www.trilux.com/altigog2)



ALTIGO WD

WALL AND CEILING LUMINAIRES



### Altigo WD

**Mounting type**  
Surface-mounted  
Recessed

**Mounting location**  
Outdoor ceiling  
Outdoor wall

**Beam characteristic**  
symmetric narrow  
rotationally symmetric wide  
rotationally symmetric narrow  
rotationally symmetric medium wide

**Luminaire luminous flux**  
300 - 4,000 lm

**Colour rendering index | Light colour**  
Ra > 80  
3,000 K  
4,000 K

**Service life**  
L80 = 50,000 h

**Luminaire colour**  
anthracite

**Accessories**  
Connectors  
Control gear  
Mounting accessories

CE UK IP65

# CONTACTS

## **TRILUX GmbH & Co. KG**

Heidestrase · D-59759 Arnsberg

Postfach 19 60 · D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

[www.trilux.com/en](http://www.trilux.com/en)

## **SiSEL Mühendislik Elektronik San. ve Tic. A.ş.**

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

[www.endalight.com](http://www.endalight.com)

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.